



# CVX CONSERVATION ROOF WINDOW

# Brite

## Applicable

In public and domestic buildings

In heated, inhabited rooms

In roof pitch range of 15°-90°

Suitable on all roofings with proper flashing

## Features

Centre pivot

Ventilation valve

Toughened outer glass

Black external profiles and black glazing bar

Extra sliding gasket

Elegant bottom handle

Two passive ventilation positions via handle

Easy installation

10 year guarantee

## Material | Wood and finishing

Kiln-dried laminated pine wood

Timber from FSC certified forests

Fungicide protection

Double layer acrylic lacquer

## Cover parts

Aluminium, lacquered, RAL 9005

## Handle

Ergonomically designed moulded zinc handle, lacquered

## Hinge

Pivot hinge



VARIANT	700
<b>Pane</b>	
Construction	4-16-4H
24 mm double glazing	■
Low E	■
Gas (argon)	■
Toughened	■
U <sub>g</sub> (W/m <sup>2</sup> K)	1.1
Total solar energy transmittance	0.60
U <sub>w</sub> (W/m <sup>2</sup> K)	1.4
Water tightness	E1350
Air permeability	Class 4
Resistance to wind load	Class C4
Sound reduction	32 (-1,-5) dB
<b>Colour</b>	
Natural wood	■

## MEASURES

CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m <sup>2</sup>
CVXC2A	55 x 78 cm	55 cm	77,8 cm	39,8 cm	64,9 cm	37,3 cm	59 cm	0.220
CVXC4A	55 x 98 cm	55 cm	97,8 cm	39,8 cm	84,9 cm	37,3 cm	79 cm	0.295
CVXF6A	66 x 118 cm	66 cm	117,8 cm	50,8 cm	104,9 cm	48,3 cm	99 cm	0.478
CVXM4A	78 x 98 cm	78 cm	97,8 cm	62,8 cm	84,9 cm	60,3 cm	79 cm	0.476
CVXM6A	78 x 118 cm	78 cm	117,8 cm	62,8 cm	104,9 cm	60,3 cm	99 cm	0.597
CVXM8A	78 x 140 cm	78 cm	139,8 cm	62,8 cm	126,9 cm	60,3 cm	121 cm	0.729
CVXS6A	114 x 118 cm	114 cm	117,8 cm	98,8 cm	104,9 cm	96,3 cm	99 cm	0.953

## FLASHING COMPATIBILITY TABLE

SIZE CODE	SLATE	TILE	UNIVERSAL	COMBI	
C2A	SFXC2A	TFXC2A	UFXC2A	UCXC2AxxE	UCXC2AxE
C4A	SFXC4A	TFXC4A	UFXC4A	UCXC4AxxE	UCXC4AxE
F6A	SFXF6A	TFXF6A	UFXF6A		
M4A	SFXM4A	TFXM4A	UFXM4A		
M6A	SFXM6A	TFXM6A	UFXM6A	UCXM6AxxE	UCXM6AxE
M8A	SFXM8A	TFXM8A	UFXM8A	UCXM8AxxE	UCXM8AxE
S6A	SFXS6A	TFXS6A	UFXS6A		

## BLIND COMPATIBILITY TABLE

BLACKOUT	ROLLER	AWNING
RURC2A	RARCXA	MIRCXA
RURC4A	RARCXA	MIRCXA
RURF6A	RARFXA	MIRFXA
RURM4A	RARMXA	MIRMXA
RURM6A	RARMXA	MIRMXA
RURM8A	RARMXA	MIRMXA
RURS6A	RARSXA	MIRSXA